



DETAIL A



DETAIL A

- NOTE :
1. CONTROLLING DIMENSION : mm
  2. LEAD FRAME MATERIAL : OLIN C7025
  3. DIMENSION "D" DOES NOT INCLUDE MOLD FLASH, TIE BAR BURRS AND GATE BURRS. MOLD FLASH, TIE BAR BURRS AND GATE BURRS SHALL NOT EXCEED 0.006"[0.15mm] PER END DIMENSION "E1" DOES NOT INCLUDE INTERLEAD FLASH. INTERLEAD FLASH SHALL NOT EXCEED 0.010"[0.25mm] PER SIDE.
  4. DIMENSION "b" DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.003"[0.08mm] TOTAL IN EXCESS OF THE "b" DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSION AND AN ADJACENT LEAD TO BE 0.0028"[0.07mm]
  5. TOLERANCE : ±0.010"[0.25mm] UNLESS OTHERWISE SPECIFIED.
  6. OTHERWISE DIMENSION FOLLOW ACCEPTABLE SPEC.

SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	—	—	1.20	—	—	0.047
A1	0.05	—	0.15	0.002	—	0.006
A2	0.80	1.00	1.05	0.031	0.039	0.041
b	0.19	—	0.30	0.007	—	0.012
C	0.09	—	0.20	0.004	—	0.008
D	7.70	7.80	7.90	0.303	0.307	0.311
E	—	6.40	—	—	0.252	—
E1	4.30	4.40	4.50	0.170	0.173	0.177
e	—	0.65	—	—	0.026	—
L	0.45	0.60	0.75	0.018	0.024	0.030
L1	—	1.00	—	—	0.039	—
y	—	—	0.076	—	—	0.003
Ø	0°	—	8°	0°	—	8°

PAD SIZE	EXPOSED PAD DIMENSION (inch)					
	D1			E2		
	MIN	NOM	MAX	MIN	NOM	MAX
A.)190x118mil	0.170	—	—	0.098	—	—
B.)190x122mil	0.170	—	—	0.102	—	—

CUSTOMER : **LINGSEN** 5-1 NAN 2ND ROAD T.E.P.Z PRECISION IND., LTD TAICHUNG, TAIWAN R. O. C

APPROVED BY: *Sandy Sue* DATE: 07/17/08  
 CHECK BY: *Jaffery Ho* DATE: 07/21/08  
 APPROVAL: *Micro Lin* DATE: 07/21/08  
 APPROVAL: *Andy Yang* DATE: 07/23/08

TITLE: 24L TSSOP PP PACKAGE OUTLINE DRAWING (4.4mm)

DWG. NO. PO-TSSOP-013 REV. 3  
 UNIT : mm SCALE : 15/1 SHEET 1 OF 1